

For More Info

Click Here --->



→ 352F

PROFESSIONAL SERIES TABLETOP FOLDER · dual roller friction feed system folds a wide variety of stocks, including carbonless sheets · adjusts in seconds for standard and custom folds · variable speed control · powered exit conveyor · sheet separation from top of fanned stack · polyurethane foam rollers eliminate the need for fold roller pressure settings · heavy-duty, non-flexing side frames · needle bearings for high speed production · options include an extended delivery system, crossfold for right-angle folding, and slitting, scoring, and perforating attachments

Dimensions (D x W x H): 22 ¼ x 41 ¾ x 14 ½ inches, Shipping weight: 105 lbs.




DUAL FEED ROLLERS



The dual roller feed system folds a wide range of stock.

POWERED CONVEYOR



A powered exit conveyor ensures smooth ejection of folded paper.

→ 352F

Speed	22,000 sheets/hr*
Paper size	2" x 2 ¾" to 14" x 21 ¼"
Paper weight	13 to 110 lbs.*
Sheet capacity	300*
Power supply	115 V, 60 Hz

* may vary due to variations in paper and power supply

Dealer:



3134 Industry Drive
North Charleston, South Carolina 29418
800-223-2508, fax: 843-552-2974
www.mbmcorp.com



1 Regan Road, unit 12
Brampton, Ontario L7A 1B8
800-387-2528, fax: 905-840-1114
www.ideal-mbm.com